






Antriebsrollen für klassische H-D® - Polizeisirenen



Vorderrad-Ausführung (im Regelfall mit Rechts-Gewinde)



	<table border="0"> <tr> <td>TYPE</td> <td>38F</td> <td></td> </tr> <tr> <td>Part-N°</td> <td>91168-40</td> <td></td> </tr> <tr> <td>Length</td> <td>1.3/8" (35mm)</td> <td></td> </tr> <tr> <td>Diameter (max)</td> <td>1." (25,4mm)</td> <td>(conical)</td> </tr> <tr> <td>Thread</td> <td>7/16"-20 UNF</td> <td></td> </tr> </table>	TYPE	38F		Part-N°	91168-40		Length	1.3/8" (35mm)		Diameter (max)	1." (25,4mm)	(conical)	Thread	7/16"-20 UNF		
TYPE	38F																
Part-N°	91168-40																
Length	1.3/8" (35mm)																
Diameter (max)	1." (25,4mm)	(conical)															
Thread	7/16"-20 UNF																







Type	38F - XL	
Part-N°	tbd	
Length	2.1/4" (57mm)	
Diameter (max)	1." (25,4mm) / conical	
Thread	7/16"-20 UNF	

	<table border="0"> <tr> <td>TYPE</td> <td>58F</td> <td></td> </tr> <tr> <td>Part-N°</td> <td>91168-58</td> <td></td> </tr> <tr> <td>Length</td> <td>1.1/8" (28,3mm)</td> <td></td> </tr> <tr> <td>Diameter (max)</td> <td>15/16." (24,0mm)</td> <td></td> </tr> <tr> <td>Thread</td> <td>7/16"-20 UNF</td> <td></td> </tr> </table>	TYPE	58F		Part-N°	91168-58		Length	1.1/8" (28,3mm)		Diameter (max)	15/16." (24,0mm)		Thread	7/16"-20 UNF		
TYPE	58F																
Part-N°	91168-58																
Length	1.1/8" (28,3mm)																
Diameter (max)	15/16." (24,0mm)																
Thread	7/16"-20 UNF																

Hinterrad-Ausführung (im Regelfall mit Links-Gewinde)

	<table border="0"> <tr> <td>TYPE</td> <td>38R</td> <td></td> </tr> <tr> <td>Part-N°</td> <td>91168-39</td> <td></td> </tr> <tr> <td>Length</td> <td>1.1/4" (32mm)</td> <td></td> </tr> <tr> <td>Diameter (max)</td> <td>1." (25,4mm)</td> <td>(conical)</td> </tr> <tr> <td>Thread</td> <td>7/16"-20 UNF LH LEFT-HAND</td> <td></td> </tr> </table>	TYPE	38R		Part-N°	91168-39		Length	1.1/4" (32mm)		Diameter (max)	1." (25,4mm)	(conical)	Thread	7/16"-20 UNF LH LEFT-HAND		
TYPE	38R																
Part-N°	91168-39																
Length	1.1/4" (32mm)																
Diameter (max)	1." (25,4mm)	(conical)															
Thread	7/16"-20 UNF LH LEFT-HAND																

	<table border="0"> <tr> <td>TYPE</td> <td>49R</td> <td></td> </tr> <tr> <td>Part-N°</td> <td>91168-49</td> <td></td> </tr> <tr> <td>Length</td> <td>1.3/4" (44,7mm)</td> <td></td> </tr> <tr> <td>Ø (max)</td> <td>1.1/16" (27mm)</td> <td>(conical)</td> </tr> <tr> <td>Thread</td> <td>1/2"-20 UNF LH</td> <td>LEFT-HAND</td> </tr> </table>	TYPE	49R		Part-N°	91168-49		Length	1.3/4" (44,7mm)		Ø (max)	1.1/16" (27mm)	(conical)	Thread	1/2"-20 UNF LH	LEFT-HAND	
TYPE	49R																
Part-N°	91168-49																
Length	1.3/4" (44,7mm)																
Ø (max)	1.1/16" (27mm)	(conical)															
Thread	1/2"-20 UNF LH	LEFT-HAND															

	<table border="0"> <tr> <td>TYPE</td> <td>58R (short)</td> <td>67R (long)</td> <td></td> </tr> <tr> <td>Part-N°</td> <td>91168-59</td> <td>91168-67</td> <td></td> </tr> <tr> <td>Length</td> <td>1.1/8" (28,3mm)</td> <td>1.3/4" (44,7mm)</td> <td></td> </tr> <tr> <td>Diameter (max)</td> <td colspan="2">15/16." (24,0mm)</td> <td></td> </tr> <tr> <td>Thread</td> <td colspan="2">7/16"-20 UNF LH LEFT-HAND</td> <td></td> </tr> </table>	TYPE	58R (short)	67R (long)		Part-N°	91168-59	91168-67		Length	1.1/8" (28,3mm)	1.3/4" (44,7mm)		Diameter (max)	15/16." (24,0mm)			Thread	7/16"-20 UNF LH LEFT-HAND		
TYPE	58R (short)	67R (long)																			
Part-N°	91168-59	91168-67																			
Length	1.1/8" (28,3mm)	1.3/4" (44,7mm)																			
Diameter (max)	15/16." (24,0mm)																				
Thread	7/16"-20 UNF LH LEFT-HAND		